



D200



D210C



S920

Peso e Dimensioni

(L x W x H): 121mm x 72mm x 22.5mm
Peso: 165g

(L x W x H): 162.5mm x 80mm x 56mm
Peso: 360g with battery

(L x W x H): 150 x 78 x 46 mm
Peso: 330g

Display

2.4 inch TFT LCD

2.8 inch TFT colour LCD pixels;
e-signature (optional)

3.5 inch 240 x 320 pixels color TFT LCD
Capture functionality



Cellulare Wireless

Wi-Fi+Bluetooth

Bluetooth 4.0 / Wi-Fi / Carta SIM

Bluetooth 4.0 / Wi-Fi / Carta SIM

Energia e Batteria

Batteria: Li-Ion , 1300mAh, 3,7 V

Batteria: Li-Ion battery 2300mAh, 7.4V
Input: 100 - 240V AC, 50 / 60 Hz, 1.5A
Output: 9VDC, 1A

Batteria: Li-Ion battery 2600mAh 3.7V
Input: 100~240VAC, 50Hz / 60Hz, 0.2A
Output: 5V DC, 1A

Card brands



Letture di carte

Magnetico: Triple track (Track1 / 2 / 3), Bidirezionale
Chip: EMV200 e PBOC 2.0 certificato
Contactless: 13.56MHz, ISO14443, Type A/B PayPass, payWav e PBOC certificato

Magnetic Card Reader: Track 1 / 2 / 3, bi-directional, Smart Card Reader Physical
Contactless: MasterCard PayPass & Visa payWave, ISO / IEC 14443 Type A / B, Battery, Mifare®, Felica, NFC

Magnetic Card Reader: Track 1 / 2 / 3, bi-directional
Smart Card Reader: EMV L1 & L2 certified
Contactless: MasterCard PayPass & Visa payWave / American Express ExpressPay / Discover DPAS / Interac Flash / ISO/IEC 14443 Type A/B, Mifare®, Felica, NFC

Stampante

No

Thermal printer, speed: 18 lines per second;
Paper roll width / diameter: 58mm / 40mm

Super fast thermal printer (18+ lps)
Paper roll flexibility: 58mm / 25mm (standard) or 40mm (optional)

Processore

32-bit secure processor, 96MHz

32-bit ARM11

32-bit ARM 11

Memoria

64MB (32MB Flash, 32MB SDRAM)

192MB (128MB Flash, 64MB DDR);
Micro SD (TF card) up to 32GB

192MB standard (128MB Flash, 64MB DDR)
Micro SD (TF card) up to 32GB

Tastiera

Touch-button input
10 numeric & 5 function keys

10 numeric keys & 8 function keys

10 numeric & letter keys, 5 dedicated function keys
Beautiful back lighting

Card slots

1 SAM & 1SAM / SIM

2 SAMs, 1 SIM, 1 microSD

2 SAMs & 1 SIM
or 1 SAM & Dual SIM

Porte Periferiche

1 mini USB;
1 RS232

1 x Micro USB (OTG);
1 x Mini USB (Rs232);
1 x Power port

1 Micro USB

Sicurezza

PCI PTS 3.x certified
SRED

PCI PTS 4.x certified

DUKPT, Master/Session, 3DES
ANSI / ISO9564 Format 0, 1, 3
PIN Ciphered Key Algorithm
ANSI X 9.9 / X9.19 MAC Algorithm

Environmental

0°C ~ 50°C (32°F ~ 122°F)operating t°
-20°C to 70°C (-4°F to 158°F)storage t°
10% to 93% relative humidity, non-condensing

-10°C to 50°C (14°F to 122°F) operating temperature
-20°C to 70°C (-4°F to 158°F) storage temperature
10% to 93% relative humidity, non-condensing

0°C to 50°C (32°F to 122°F) operating temperature
-20°C to 70°C (-4°F to 158°F) storage temperature
10% to 93% relative humidity, non-condensing



D200



D210C



S920